

Thread two 3½" carriage bolts through the two lower holes in each leg and through the long slot in each extension. Place a large fender washer and a wood wing nut on the threaded end of each bolt and tighten securely. Make sure the metal hex nut that is embedded in the wood wing nut is <u>on the</u> outside.

(3)

•TIP: To "set" the bolts when you first complete this step lightly tap each carriage bolt head with a hammer while tightening the wood wing nuts with your other hand. This will slightly sink the carriage bolt heads into the wood where they will grip well and not work their way out. Most important, it will help hold the extensions in place more securely for your safety!

You may perform the steps labelled "Assemble extensions in leg units" (3) and "Attach leg units" (4) in any order.

"Square up" the leg assemblies to the LEVEL-it® top. Hold the diagonal braces in place against the bottom side of the LEVEL-it® top and the lower braces as shown. Fasten the two diagonal braces with #8 X 1½" washer head screws as shown.

Thread a 3½" carriage bolt down through the counterbored holes in the **LEVEL-it**® top and through the holes in the middles of the upper braces. Place a flat washer and a nut over the ends of each bolt and tighten securely with a wrench.

Remember – lower braces face IN (see picture)

note how tops of legs are parallel to bottom edge of LEVEL-it® top

0


0

You may perform the steps labelled "Assemble extensions in leg units" (3) and "Attach leg units" (4) in any order.

video instructions are at this webpage: http://www.level-it.com/lvl/assembly.php

complete photographic assembly instructions are at: http://www.level-it.com/dcs\_fr/instruct.php

a webpage of assembly instructions which may be translated into your language is at: http://www.level-it.com/usg/



© 2012 ASHER INDUSTRIES Ltd.

(5) REUSTRIES Ltd.

Attach leg units

(7a)

wood wingnuts

look like thi




# Tips for LEVEL-it® users

## Finishing tips

Sand all rough edges and corners. For use outside in wet weather disassemble leg extensions and apply a clear solvent or acrylic base sealer to all wood parts. When parts are dry reassemble leg extensions.

#### Tips for use

The LEVEL-it<sup>®</sup> has slots down the center of the top. This is so you can mount tools, jigs, our **DOG-it<sup>™</sup>**, our **TOP-it<sup>™</sup>** and other things directly on it! You can also mount your own jigs, small bench tools, hold down clamps, etc. directly onto your LEVEL-it<sup>®</sup>. Some items will first need to be mounted to a suitable board (such as a piece of scrap plywood) and then that board will mount directly onto your LEVEL-it<sup>®</sup> as shown directly below. (Use screws or nuts & bolts to mount as appropriate)



Make sure to <u>CHECK THE WING NUTS ON THE LEG EXTENSIONS OFTEN</u> to make sure they are tight. Loose wing nuts will not support your work.

An occasional drop of oil on each of the eight leg extension carriage bolts will keep them working very smoothly, particularly in wet locations.

### MAXIMUM WEIGHT CAPACITY per LEVEL-it® is 450 POUNDS

# Always work safely and carefully. Follow the instructions for all of your tools to avoid accidents and injury to yourself and/or others.

Make a  $\textbf{DOG-it}^{\texttt{TM}}$  bench stop. It is like a classic "Bench Dog" and used to help hold your work.

